

Verti-Drain® 7621

The 7621 Verti-Drain features a heavy-duty gearbox & hydraulic depth control to allow for working depth changes on the move. It is well suited to the toughest of soil conditions, with a 210cm / 83" working width it has the ability to cover large areas with ease.



Specifications

SKU	7621
Working width (m)	2.1
Working width (inch)	83
Max. Working depth (mm)	400
Max. Working depth (inch)	16
Weight (kg)	1565
Weight (lbs)	3450
Hole distance with 12 mm tines (mm)	65
Hole distance with 1 2 x 6 inch tines (inch)	2.5
Hole distance with 24 mm tines (mm)	129
Hole distance with 1 x 16 inch tines (inch)	5
Hole spacing distance driving direction (mm)	50-195
Hole spacing distance driving direction (inch)	2 - 7-1/2
Max diameter solid tine (mm)	24 x 400
Max diameter solid tine (inch)	1 x 16
Max diameter hollow tine (mm)	32 x 300
Max diameter hollow tine (inch)	1-1/4 x 12
Min. Tractor HP required	55
Min. lifting capacity (kg)	2000
Min. lifting capacity (LBS)	4408
Max. capacity with spacing 65 mm (m ² hr)	1575
Max. capacity with spacing 2-1 2 inch (ft ² hr)	16953
Three-point hitch	3-point CAT 2
Rpm Max.	500
Gear case oil	80W90 - 6.5
Lubricant	EP2
Slip clutch setting	1100 Nm